

KITE SHIP: PRELIMINARY INVESTIGATION ON POWER GENERATION

SAMSOL AZHAR BIN ZAKARIA

A dissertation submitted in partial fulfillment of the
requirements for the award of the degree of
Master of Engineering (Marine Technology)

Faculty of Mechanical Engineering
Universiti Teknologi Malaysia

MAY 2009

To my great Father and Mother, Brothers and Sisters, my Dear Wife and my Sons
and Daughter, whose prayers always afforded me the power to accomplish this
work. To all I dedicate this work with great respect and love.

ACKNOWLEDGEMENT

All praise to Allah SWT, the Most Gracious and Most Merciful, Who has created the mankind with knowledge, wisdom and power. Being the best creation of Allah, one still has to depend on other for many aspects directly and indirectly. This is, however, not an exception that during the course of study the author received so much help, cooperation and encouragement that need to duly acknowledgement.

In preparing this thesis, I was in contact with many people, academicians and practitioner. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my supervisor Tn Hj. Yahya Samian, for encouragement, guidance, friendship and valuable comments in completion of this work. Without your guidance, support and interest this dissertation would not have been the same as presented here.

A warmest gratitude and special dedication to my family, mother and sister for their understanding, patient and support. A special dedication to my loving wife, Nazzattul Shyma for her support, love and joy. And also for my loving sons and daughter, Muhammad Afif Aiman , Muhammad Fairul Adam and Saidattul Sofea for their understanding, patient and love.

Then, special gratitude to all UniKL MIMET staffs , Malaysian Meteorology Department, Zeppelin SkySails Sales & Services personel especially Ms. Sandra Becker, Mr. Shamsul Afendi at Starclyde University and UTM lecturers, many thanks for my friends who are unnamed here and were involved directly or indirectly for giving their critics and suggestion.

ABSTRACT

This research project is carried out with the purpose of investigating the application of kite ship system operating within Malaysian water and weather environment. This study began with the analyzing of the weather characteristic such as wind speed, wind direction and frequency in selected South China Sea area based on the data given by the Malaysian Meteorological Department. It then followed with the study on technical knowhow in determining the additional propulsive force generated to the ship by the flying kite. The additional propulsive power was then translated into the amount of fuel saving that a ship can achieved. This has in turns enabled the economic analysis to be carried out. To investigate the techno economic feasibility of the kite ship system, a case study was made to a typical medium size vessel operating within the selected area. The result of this study indicated that, the average speed and frequency of wind in South China Sea is capable for launching and modestly operating the kite ship system. The most suitable local shipping route to apply kite ship system is when the prevailing wind direction is coming from Northeast from January until March and winds direction coming from Southwest from July to September. In this study, the shipping route selected for an analysis is Sepangar – Singapore - Sepangar. Based on the techno economic analysis, with the investment cost of kite systems at around Euro 495,000.00 and the fuel saving due to wind force at 16 %, the break even of total investment can be achieved within four to six years depending on fuel price.

ABSTRAK

Kajian penyelidikan ini dijalankan adalah untuk menyiasat mengenai aplikasi sistem layang-layang kapal yang beroperasi di perairan dan keadaan cuaca di Malaysia. Kajian ini dimulakan dengan penganalisan keadaan cuaca seperti halaju, arah dan kekerapan angin di kawasan yang terpilih di Laut Cina Selatan berdasar kepada data yang diberikan oleh Jabatan Meteorologi Malaysia. Seterusnya, ia disusuli dengan kajian pengetahuan teknikal untuk mencari kuasa rejangan tambahan yang dihasilkan oleh sistem layang-layang terhadap kapal. Kuasa tambahan ini kemudiannya akan diterjemahkan kepada jumlah penjimatan bahan api kapal yang boleh dicapai. Ini seterusnya membolehkan kajian ekonomi dijalankan. Untuk menyiasat kebolehan pelaksanaan secara tekno ekonomi untuk sistem layang-layang kapal ini, kajian kes dijalankan keatas kapal yang bersaiz sederhana dan beroperasi di lingkungan kawasan yang dipilih. Hasil keputusan daripada kajian ini menunjukkan, purata halaju dan kekerapan angin di Laut Cina Selatan adalah berupaya untuk melancar dan beroperasi secara sederhana untuk sistem layang-layang kapal ini. Laluan kapal tempatan yang paling sesuai untuk menggunakan sistem layang-layang ini adalah apabila arah angin lazim bertiup dari arah Timur Laut bermula daripada Januari hingga Mac dan arah angin lazim datang daripada arah Barat Daya yang bermula daripada Julai hingga September. Di dalam kajian ini, laluan kapal yang dipilih adalah Sepangar – Singapore –Sepangar. Berdasarkan kepada kajian tekno ekonomi, dengan kos pelaburan untuk sistem layang-layang kapal lebih kurang Euro 495,000.00 dan jumlah penjimatan bahan api disebabkan oleh daya angin adalah 16%, pulangan untuk jumlah pelaburan boleh dicapai antara empat hingga enam tahun bergantung kepada harga minyak.

TABLE OF CONTENTS

	TITLE`	PAGE
	SUPERVISOR’S DECLARATION	i
	TITLE PAGE	ii
	DECLARATION	iii
	DEDICATION	iv
	ACKNOWLEDGEMENT	v
	ABSTRACT	vi
	ABSTRAK	vii
	TABLE OF CONTENTS	viii
	LIST OF FIGURES	xiii
	LIST OF TABLES	xvi
	LIST OF NOMENCLATURE	xvii
	LIST OF APPENDICES	xx
1	INTRODUCTION	1
	1.1 Background of Study	1-2
	1.2 Problem Statement	2
	1.3 Objectives	3

1.4	Scope of the Research	3
1.5	Expected Benefit	4
2	LITERATURE REVIEW	5
2.1	Introduction	5
2.2	Historical background	6
2.3	Renewal Energy from Wind	7
2.4	Development of Kite Ship-Past and Present	10
2.5	Physic and aerodynamic theory behind kite flight	13
2.5.1	Basic aerofoil section characteristic	15
2.5.2	Lift and Drag	17
2.5.3	Reduction in Induced Drag	20
2.5.4	Lifting Surface	21
2.5.5	Vortex Theory	22
2.5.6	Optimum Lift and Drag	24
2.5.7	Aspect Ratio	25
2.5.8	Low Flying Speed	26
2.6	Wind	26
2.6.1	The structure of wind	27
2.6.2	Wind characteristic	27
2.6.3	Wind direction	28
2.6.4	Wind speed	29
2.6.5	Wind force	29
2.6.6	Air density	31
2.7	Kite Design	32

2.7.1	Kite altitudes	33
2.7.2	Kite area and size	33
2.7.3	Kite Lift Coefficient (C_L)	34
2.7.4	Kite Drag Coefficient (C_D)	36
2.8	Forces acting on ship	37
2.8.1	Kite operations on ship	39
2.9	Circular motion	40
2.10	Flight Envelope	42
2.11	Formula of True Wind and Apparent Speed	47
2.12	Formula of Relative Velocity, (V_{rel})	48
2.13	Kite Lift Coefficient Correction	51
2.14	Kite Drag Coefficient Correction	53
2.15	Formula of Lift, Drag and Traction Force	54
2.16	Ship powering	55
2.17	Conclusion	57
3	METHODOLOGY	58
3.1	Introduction	58
3.2	Framework of Study	59
3.3	Methodology	60
3.4	Schedule of activities and Project Flow Chart	62
3.5	Thesis Organization	63
4	TRACTION FORCE ESTIMATION	65
4.1	Introduction	65
4.2	Important Assumption	65

4.3	Traction Force Algorithm	66
4.4	Example of Calculation	69
4.4.1	Calculation of Apparent Wind Speed	71
4.4.2	Calculation of Relative Velocity, V_{rel}	71
4.4.3	Calculation of Lift and Drag Coefficient	74
4.4.4	Calculation of Forces	74
4.4.5	Ship powering estimation	76
4.5	Program Development	77
4.6	Result of Calculation	81
4.7	Conclusion	82
5	WEATHER ANALYSIS	83
5.1	Introduction	83
5.2	Data Collection	84
5.2.1	Local Weather Data	84
5.2.2	Kite Data	86
5.2.3	Ship Data	89
5.2.4	Ship Route	92
5.3	Analysis	92
5.3.1	Wind Direction	93
5.3.2	Wind Speed and Frequency	98
5.3.3	Potential Sailing Route	101
5.4	Conclusion	103

6	ECONOMIC ANALYSIS	105
6.1	Introduction	105
6.2	Data for Analysis	106
6.3	Power Saving Analysis	108
6.4	Economic Analysis	111
6.4.1	Fuel saving	112
6.4.2	Installation, Maintenance and Service Cost	112
6.5	Conclusion	116
7	DISCUSSION AND CONCLUSION	118
7.1	Discussion	118
7.2	Future Recommendation	119
7.3	Conclusion	119
	REFERENCES	120
	Appendices A –E	123

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	The Wright's Brothers Kite	6
2.2	Schematic drawing of different renewal wine energy	8
2.3	Typical sailing devices	9
2.4	Diagram of Parafoil kite	15
2.5	Lift –Drag Diagram	16
2.6	Classification of drag	17
2.7	Lift, drag and moment coefficients and moment coefficient	20
2.8	Pradtl's classical lifting line theory	21
2.9	Airflow around an aerofoil	22
2.10	Vortex lines	23
2.11	Direction of wind and possible ship course	28
2.12	Free Body Diagram of the kite	30
2.13	Downwash effects on kite	34
2.14	Skysail Kite Ship system	38
2.15	Trajectory of flying kite with manoeuvre in a figure of "eight path"	40
2.16	Object in circular motion	41
2.17	Flight Envelope (FE)	43

2.18	Iso-power and Iso-gradient lines	44
2.19	Flying maneuvers	45
2.20	Kite position in Flight Envelope	45
2.21	Kite from top view of Flight Envelope	46
2.22	Apparent wind components and angle of attack(α)	49
2.23	Kite span with curvature angle	52
3.1	Research stages	60
3.2	Project Scheduling PGP1 (First Semester)	62
3.3	Project Scheduling PGP2 (First Semester)	63
4.1	Estimation of kite traction force flow chart	68
4.2	Main Program Flow Chart	78
4.3	Read Input Flow Chart	78
4.4	Calculation Process Flow Chart	79
4.5	Display Output Flow Chart	80
4.6	Save Output Flow Chart	80
5.1	Data collection and observation at South China Sea (Latitude 0.0 – 7.0 ° N and Longitude 103.0-120)	85
5.2	SkySail , Towing kite	87
5.3	SkySails, towing kite with double-wall profile	88
5.4	Local Ship Route at South China Sea	92
5.5	Radar Chart for wind speed 7 knots for year 2005- 2008	93
5.6	Dominant wind direction from NE and S.	94
5.7	Northeast (NE) wind: (a) January 2007 & (b) March 2007	96
5.8	Southwest (SW) wind :(a) July 2007 & (b) September 2007	97

5.9	Result of average wind speed: (a) January 2008 & (b) Year 2008	99
5.10	Average wind speed: (a) NE (50 degree) & (b) SW (220 degree)	100
5.11	Wind direction onto ship course	101
5.12	Local Shipping Route for Bunga Siantan	102
6.1	Fuel price for IFO 380 in Singapore	114
6.2	Break Even Graph (without fuel price increment)	115
6.3	Break Even Graph (with fuel price increment)	116

LIST OF TABLES

TABLE NO.	TITLE	PAGE
4.1	Sample of kite data	69
4.2	Wind, kite position and ship data	70
4.3	Ship data	70
4.4	Result of power generate by kite	81
4.5	Result of power saving	82
5.1	Sample of Wind data for Day 1 st January ,2005.	86
5.2	SkySails,Kite Data	88
5.3	Operating Conditions SkySails SKS C 160	89
5.4	SkySails Product for Cargo Ship	90
5.5	Skysails Standard conditions	90
5.6	Sample of Local Ship Data	91
5.7	Summary of dominant wind direction at 3-7 Beaufort in year 2005 -2008	95
5.8	Summary of average wind speed for year 2005 to 2008	99
5.9	Average wind speed for each route onto the ship direction	103
6.1	Ship data	106
6.2	Kite data	107
6.3	Wind data	107
6.4	Apparent wind speed	108

6.5	Relative wind speed, V_{rel}	109
6.6	Traction force generated by kite	110
6.7	Percentage of power saving	110
6.8	Total price of fuel consumption saving	111
6.9	Result of Potential Saving Analysis	112
6.10	SkySail System -Breakdown cost	113
6.11	Initial cost breakdown	114

LIST OF NOMENCLATURE

Abbreviation

FE	- Flight Envelope
NE	- Northeast
S	- South
SW	- Southwest
BP	- British Petroleum

Symbols

Re	- Reynolds number
C_L	- Lift coefficient
C_D	- Drag coefficient
C_M	- Moment coefficient
Γ	- Circulation
F_L	- Lifting Force
F_D	- Drag Force
T_a	- Traction force
V	- Airflow at the towing kite

A	- Surface area of the towing kite
ρ_a	- Air density
AR	- Aspect ratio
C_{Lo}	- Lift slope coefficient
C_{Do}	- Drag slope coefficient
α	- Angle of attack
α_L	- Zero lift angle of attack
s	- Kite span
W	- True wind speed
$W_{(z)}$	- Wind speed at altitude z above (sea) surface
u_{ref}	- Wind speed at reference level
z_{ref}	- Reference level
z_o	- Surface roughness (depending on wave height)
$V_{(A)}$	- Propeller pitch
V_{rel}	- Relative velocity
V_t	- Tangential velocity
V_{r-z}	- Radial velocity at Z direction
V_{t-x}	- Tangential velocity at X direction
V_{t-y}	- Tangential velocity at Y direction
V_{x-k}	- Kite speed at X direction
V_{y-k}	- Kite speed at Y direction
V_{y-w}	- True wind at Y direction
V_k	- Kite's own speed
γ	- Kite flying direction
$\dot{\theta}, \dot{\phi}$	- Kite's own speed in term of circular motion

$C_{L,c}$	- 3D lift coefficient of curved wing
ζ	- Angle of curvature
ε	- Angle of between kite centerline and kite edge
R	- Length of lines between gondola and kite
b	- Constructed span
$C_{D,l}$	- Drag coefficients of lines between gondola and kite
d	- Diameter of individual lines
α_l	- Angle of attack between relative speed and kite line
$C_{D_{zl}}^s$	- Zero lift surface irregularities and fabric roughness drag coefficient
$C_{D_{zl}}^n$	- Zero lift inlet drag coefficient due to open airfoil nose
h	- Height of the inlet
c	- Chord length of the kite or wing profile
F_s	- Vertical component of traction force acting on ship
β	- Tow line drift angle
V_a	- Speed of advance
R_T	- Ship resistance
T	- Thrust
P_E	- Effective power
P_T	- Thrust power
P_D	- Delivered power
P_B	- Brake power
η_H	- Hull efficiency
η_R	- Relative rotative efficiency

- η_o - Propeller efficiency –open water
- η_B - Propeller efficiency- behind hull
- η_S - Shaft efficiency
- η_T - Total efficiency

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	DesignFoil Calculation Result	124
	A1 : Lift and Drag Coefficient	
	A2 : Lift and Drag Slope of NACA 4415	
B	Calculation	127
	B1: Relative Velocity Calculation	
	B2: Traction Force Calculation	
	B3: Power saving Calculation	
	B4: Source code & Input and Output for FOTRAN	
	77 programming.	
C	Data	139
	C1 : Ship Data	
	C2: Ship Resistance Data	
D	Techno Economic analysis	144

CHAPTER 1

INTRODUCTION

1.1 Background of Study

Today, fuel costs become sufficiently high and governmental air and water quality regulations became sufficiently odious. The latest price increases have placed tremendous cost pressure on the commercial shipping industry. There is strong evidence that recent fuel cost increases aren't going to be temporary, and environmental restrictions will become increasingly in law implementation. In April 2008, IMO approved a reduction in sulfur emissions for the shipping industry [1]. Meaning, if no fuel is combusted, there are no emission. Obviously, the commercial shipping industry need to look forward alternative power as an assist to petroleum powered vessels towards to year 2020.

One of the most recent inventions of renewable energy concept for ship is the use of kite as sailing power. Recent demonstration on the application of kite as an additional power generator for a medium size bulk carrier ship has indicated that it could reduce up to 30 percent of the vessel's fuel consumption [2]. Hence it has a great potential to be applied to local (locally operated) vessel especially during monsoon season.

However, kite ship concept is very new hence the theoretical background and experimental studies have not been widely available. This research is therefore intends to study the physics and mechanics of forces generated by the kite, taking into consideration local weather (wind) conditions. The result of the study will then be translated into potential source of additional power generation of a vessel that could reduce the fuel consumption and green house effects. The potential of its application for local ship (such as Fishing Vessel, Passenger Ferry etc) can also be explored. One of the important parameters on which fuel consumption utilize is dependent on type of local weather the vessels encounters during its voyage. The cost of fuel saved as a result of weather and ship routing are the main criteria to be analyze.

1.2 Problem Statement

In the carrying out the investigation on power generation by kite ship, several issues will be addressed as follow:

1. How forces from the sailing kite can provide additional power to ship?
2. How feasible is this concept to be implemented in vessels operating local environment?

1.3 Objectives

In addressing the above issues, this project work is therefore carried out with the following objectives:

1. To study the technical know how (physic and mechanics) on how aerodynamics forces of a flying kites is converted to propulsion forces of a ship.
2. To investigate the feasibility of this concept to be implemented for ships operating in local environment.

1.4 Scope of the Research

The scopes of this project are listed as follows:

1. Conduct literature research on Kite Ship
2. Study the technical know how (physics and mechanics) on how aerodynamics forces behind the kite flight.
3. Study mathematical modelling of kite flight and traction force calculation
4. Analysis of local weather condition in order to determine suitable shipping route.
5. Techno economic analysis for potential fuel saving.

Limitations of this research are:-

1. Theoretical analysis with no experiment.
2. Only local wind data from South Chinese Sea will be use in feasibility study.

1.5 Expected Benefit

The result of this study will be useful for knowledge and understanding on the relationship between aerodynamics forces (physics and mechanics) of flying kite with additional forces or power generated to the ship. Then, the result of this study can be translate into potential source of additional power generation for vessels operating in local environment that could reduce the fuel consumption and green house effect such as fishing vessel, general cargo, yacht , etc.

REFERENCES

- [1] IMO, Marine Environment Protection Committee, MEPC 57/4/5 *Prevention Of air Pollution from Ships*, December 2007;
- [2] Skysail Gmbh & Co. KG , *Skysail Technology Information*, February 2008;
- [3] Prof. Dr. Wubbo J. Ockels and J. Breukels , *Past , Present and Future of Kites and Energy Generation*, Delft University of Technology, The Netherlands,2007;
- [4] Best Breezes, *Kite History*, www.best-breezes.squarespace.com, October 2008;
- [5] B. R. Clayton, *Wind-Assisted Ship Propulsion*, Phys Technol 18, UK 1987;
- [6] Yasuo Yoshimura, A prospect of Sail-Assisted Fishing Boats, Japanese Society of Fisheries Science, 2002;
- [7] RINA, *Symposium on wind propulsion of commercial ships*, 1980
<http://www.rina.org.uk>;
- [8] SkySails ,*Turn Wind to profit*, <http://www.skysails.info/index.php>, January 2009;
- [9] KiteShip. Innovation in tethered flight, <http://www.kiteship.com/marine.php>, January 2009;
- [10] Stephen E. Hobbs, *A quantitative study of kite performance in natural wind with application to Kite Anemometry*, Ecology Physics Research Group, 1986;
- [11] WINTeCC Project , *Testing of the SkySails System aboard the140m Heavy Lift Multi Purpose Carrier*, <http://www.wintecc.de/index.php?id=3&=1>, November 2008;
- [12] Wubbo J. Ockels, *Laddermill, a novel concept to exploit the energy in the airspace*, Delft University of Technology, Aircraft Design 4 (2001) 81}97,2001;
- [13] Johanna Vogel-Prandtl, *Ludwig Prandtl's Biography in German*, 2006;
- [14] Jason Gibbs, *Experimental Determination of Lift and Lift Distributions for Wings In Formation Flight* , Faculty of the Virginia Polytechnic Institute and State University, 2005;

- [15] Liam Browning, *An investigation into the use of kite as an alternative form of propulsion of ships*, University of Newcastle upon Tyne, 2007;
- [16] J.S. Carlton, *Marine Propeller and Propulsion*, pp. 134-146 Butterworth Heinemann, 1994;
- [17] Joseph Katz , Allen Plotkin, *Low-Speed Aerodynamics*, Cambridge University Press, pp. 17-20, 2001;
- [18] NASA, Glenn Research Center, *Kites*, <http://www.grc.nasa.gov/WWW/K-12/airplane/kite1.html> ; December 2008;
- [19] Wellicome, J., & Wilkinson, S. , *Ship propulsive kites - an initial study* ,University of Southampton, Department of Ship Science, Faculty of Engineering and Applied Science, 1984;
- [20] Aleksandr R. Podgates & Wubbo J. Ockels, *Laddrmill sail- a new concept in sailing*, Delft University of Technology, 2008;
- [21] Professor Peter Naaijen, Vincent Koster and R.P Dallinga, *On the power savings by an auxiliary kite propulsion system*, Delft University of Technology, International Shipbuilding Progress 53 (2006) 255–279, 2006;
- [22] George Dadd, *Implementation and validation of a kite velocity prediction program*, Scholl of Engineering Science, University of Southampton, UK, 2008;
- [23] Troen, I. and E.L. Petersen *European Wind Atlas*. ISBN 87-550-1482-8. Risø National Laboratory, Roskilde, 1989;
- [24] J.S Lingard ,”Ram Air parachute design”, Martin-Baker Aircraft Co. Ltd.,Midlesea, England, 1995;
- [25] Om Prakash, “*Aerodynamics and Longitudinal stability of Parafoil/Payload system, a preliminary report by Om Prakash*”, Aerospace Engineering Department, IITB;
- [26] DesignFOIL R6_Demo, <http://www.dreeseencode.com/>, February 2009;
- [27] Malaysian Meteorological Department,
<http://www.met.gov.my/htdocs2/data/wxfcb.html#wind> , March 2009;
- [28] Pusat Hidrografi Nasional, *Carta Navigasi Elektronik* ,
<http://www.hydro.gov.my/>, March 2009 ;
- [29] Zeppelin SkySails Sales & Services GmbH & Co. KG , *Potential analysis for the type “Rhine”* , SkySails System SKS C160, 2008;

- [30] Bunkerworld, <http://www.bunkerworld.com/markets/prices/sg/sin/>, April 2009;